

# Experience The Future Today

for All Your Event



## P10/P20

### Presentation Switchers

The P series (P20 and P10) are PIXELHUE's all-new 4K presentation switchers fully featured in a compact form factor. Featuring high-quality 4K processing, the P20 and P10 are designed with a wide variety of 4K connectors, including HDMI 2.0, DP 1.2 and 12G-SDI.

















The P20 and P10 can work in switcher mode or PGM only mode. In switcher mode, a single P20 supports up to two 4Kx2K@60Hz outputs and a single P10 supports one 4Kx2K@60Hz output. In PGM only mode, the output resolution per P20 is up to 8Kx4K@60Hz and P10 is up to 8Kx2K@60Hz.











Additionally, the P20 and P10 come with dedicated AUX outputs connecting to auxiliary devices and a dedicated Multiviewer output is provided for live view of all the inputs and outputs from one display. High-performance image deinterlacing is also supported.

## U5

### Compact Event Controller

Equipped with the leading-edge core architecture and SSD(NVMe), the U5 event controller enables the most fluent and fast operations ever. With the design concept of increasing operational efficiency and satisfying the various changing needs that may arise from event scenarios, the U5 event controller comes with all the crucial functionalities that you may need. The newly-upgraded built-in software PixelFlow with always user-friendly GUI helps you manage devices, screens, layers, sources, presets more stably and easily. The magnificent interactive design maximizes user convenience and shortens your learning curve. Convenient control over multiple presentation switchers and media servers greatly simplifies your on-site deployment and brings more convenience and ease to your events. In addition, timecode generating and accepting support, timecode format conversion ability and MIDI support add extra value to all spectacles.

 4K I/O	 HDMI 2.0	 DP 1.2	 12G-SDI
 10km Distance	 UP TO 12 INPUTS	 UP TO 4 OUTPUTS	 UP TO 12 LAYERS
 HDR SDR	 DSK	 MULTIVIEWER	 FLEXIBLE CONTROL
 VIRTUAL DEVICES	 EDGE BLEND	 BEZEL COMPENSATION	 CUT & FILL

 JOINT CONTROL	 ONE CONTROLS MULTIPLE	 10:56:48:39 TIMECODE	 KVM
 PTZ	 PROGRAMMABLE LCD BUTTONS	 ENCODERS & FADERS	 FOLDABLE DESIGN
 DUAL SCREEN	 MIDI MIDI PROTOCOL		